

**SECTION 1: Identification**
**1.1. Identification**

Product form : Mixture  
 Product name : ELECTROSTATIC ENL LOW VOC GLOSS WHITE BASE  
 Product code : 171T1000

**1.2. Recommended use and restrictions on use**

Recommended use : Industrial use  
 Restrictions on use : The product is intended for professional use

**1.3. Supplier**

Sumter Coatings, Inc.  
 2410 Hwy 15 South  
 Sumter, SC 29150 - United States  
 T 803-481-3400 - F 803-481-3776  
[info@sumtercoatings.com](mailto:info@sumtercoatings.com) - [www.sumtercoatings.com](http://www.sumtercoatings.com)

**1.4. Emergency telephone number**

Emergency number : 800-255-3924 Chemtel

**SECTION 2: Hazard(s) identification**
**2.1. Classification of the substance or mixture**
**GHS US classification**

Flammable liquids Category 1	H224	Extremely flammable liquid and vapor
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Germ cell mutagenicity Category 1B	H340	May cause genetic defects
Carcinogenicity Category 1B	H350	May cause cancer

Full text of H statements : see section 16

**2.2. GHS Label elements, including precautionary statements**
**GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H224 - Extremely flammable liquid and vapor  
 H317 - May cause an allergic skin reaction  
 H319 - Causes serious eye irritation  
 H340 - May cause genetic defects  
 H350 - May cause cancer

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P233 - Keep container tightly closed.  
 P240 - Ground/Bond container and receiving equipment.  
 P241 - Use explosion-proof electrical/ventilating/lighting equipment.  
 P242 - Use only non-sparking tools.  
 P243 - Take precautionary measures against static discharge.  
 P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
 P264 - Wash hands, forearms and face thoroughly after handling.  
 P272 - Contaminated work clothing must not be allowed out of the workplace.  
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.

# 171T1000

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P302+P352 - If on skin: Wash with plenty of water.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P363 - Wash contaminated clothing before reuse.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Titanium Dioxide	(CAS.No.) 13463-67-7	15.032 – 16.702	Carc. 2, H351
METHYL N-PROPYL KETONE	(CAS.No.) 107-87-9	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319
AROMATIC 100	(CAS.No.) 64742-95-6	1 – 5	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
GLYCOL ETHER EP/PROPYL CELLOSOLVE SOLVENT	(CAS.No.) 2807-30-9	1 – 5	Flam. Liq. 3, H226 Acute Tox. 3 (Dermal), H311 Eye Irrit. 2, H319
AROMATIC 150	(CAS.No.) 64742-94-5	1 – 5	Skin Irrit. 2, H315 Asp. Tox. 1, H304
XYLENE	(CAS.No.) 1330-20-7	1.155 – 1.385	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
MINERAL SPIRITS R66/ D40	(CAS.No.) 64742-47-8	0.794 – 1.068	Flam. Liq. 3, H226 Asp. Tox. 1, H304
d'LIMONENE	(CAS.No.) 5989-27-5	0.1 – 1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317
Naphtha (petroleum), hydrotreated heavy	(CAS.No.) 64742-48-9	0.21 – 0.421	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
ethylbenzene	(CAS.No.) 100-41-4	0.225 – 0.34	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304
METHYL-ISOBUTYL KETONE	(CAS.No.) 108-10-1	0.1 – 1	Flam. Liq. 2, H225 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H335
2-BUTANONE OXIME	(CAS.No.) 96-29-7	0.1 – 1	Flam. Liq. 4, H227 Acute Tox. 4 (Dermal), H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351

# 171T1000

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

#### 4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : May cause an allergic skin reaction.
- Symptoms/effects after eye contact : Eye irritation.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Specific hazards arising from the chemical

- Fire hazard : Extremely flammable liquid and vapor.

#### 5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing dust/fume/gas/mist/vapors/spray.

##### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

# 171T1000

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures : Separate working clothes from town clothes. Launder separately. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.  
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

2-BUTANONE OXIME (96-29-7)		
Not applicable		
XYLENE (1330-20-7)		
ACGIH	Local name	Xylene, mixed isomers (Dimethylbenzene)
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
ethylbenzene (100-41-4)		
ACGIH	Local name	Ethylbenzene
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Naphtha (petroleum), hydrotreated heavy (64742-48-9)		
OSHA	OSHA PEL (TWA) (ppm)	400 ppm
d'LIMONENE (5989-27-5)		
Not applicable		
MINERAL SPIRITS R66/ D40 (64742-47-8)		
Not applicable		
Titanium Dioxide (13463-67-7)		
ACGIH	Local name	Titanium dioxide
ACGIH	ACGIH TWA (mg/m³)	10 mg/m³
ACGIH	Remark (ACGIH)	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
METHYL N-PROPYL KETONE (107-87-9)		
ACGIH	Local name	Methyl propyl ketone
ACGIH	ACGIH STEL (ppm)	150 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: Pulm func; eye irr

# 171T1000

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>METHYL N-PROPYL KETONE (107-87-9)</b>		
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	700 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>AROMATIC 100 (64742-95-6)</b>		
Not applicable		
<b>METHYL-ISOBUTYL KETONE (108-10-1)</b>		
ACGIH	Local name	Methyl isobutyl ketone
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	75 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT irr; dizziness; headache. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	410 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>AROMATIC 150 (64742-94-5)</b>		
Not applicable		
<b>GLYCOL ETHER EP/PROPYL CELLOSOLVE SOLVENT (2807-30-9)</b>		
Not applicable		

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Wear respiratory protection.

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Liquid.  
Color : white

# 171T1000

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odor	: characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 46 °F BASED ON DATA AVAILABLE FOR INGREDIANTS
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 9.97 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable liquid and vapor.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

<b>2-BUTANONE OXIME (96-29-7)</b>	
LD50 oral rat	2326 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)
LD50 dermal rabbit	> 1000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat	> 4.83 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours))
ATE US (oral)	2326 mg/kg body weight

# 171T1000

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>2-BUTANONE OXIME (96-29-7)</b>	
ATE US (dermal)	1100 mg/kg body weight
<b>XYLENE (1330-20-7)</b>	
LD50 oral rat	> 3608 mg/kg (Rat, Oral)
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
<b>ethylbenzene (100-41-4)</b>	
LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	15432 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))
ATE US (oral)	3500 mg/kg body weight
ATE US (dermal)	15432 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	17.8 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
<b>d'LIMONENE (5989-27-5)</b>	
LD50 oral rat	> 2000 mg/kg body weight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Read-across, Oral)
LD50 dermal rabbit	> 5000 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Weight of evidence, Dermal)
<b>Titanium Dioxide (13463-67-7)</b>	
LD50 oral rat	> 5000 mg/kg body weight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))
<b>METHYL N-PROPYL KETONE (107-87-9)</b>	
LD50 oral rat	1600 – 3200 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral)
LD50 dermal rabbit	6500 mg/kg (Rabbit, Dermal)
LC50 Inhalation - Rat	> 25.5 mg/l (OECD 436: Acute inhalation toxicity-acute toxic class method, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1600 mg/kg body weight
ATE US (dermal)	6500 mg/kg body weight
<b>METHYL-ISOBUTYL KETONE (108-10-1)</b>	
LD50 oral rat	2080 mg/kg (Equivalent or similar to OECD 401, Rat, Experimental value, Oral)
LD50 dermal rat	≥ 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat	8.2 – 16.4 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Experimental value, Inhalation (vapours))
ATE US (oral)	2080 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	8.2 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
<b>GLYCOL ETHER EP/PROPYL CELLOSOLVE SOLVENT (2807-30-9)</b>	
LD50 oral rat	3089 mg/kg (Rat, Oral)
LD50 dermal rabbit	873 mg/kg (Rabbit, Dermal)
ATE US (oral)	3089 mg/kg body weight
ATE US (dermal)	873 mg/kg body weight

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects.

# 171T1000

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carcinogenicity : May cause cancer.

<b>XYLENE (1330-20-7)</b>	
IARC group	3 - Not classifiable
<b>ethylbenzene (100-41-4)</b>	
IARC group	2B - Possibly carcinogenic to humans
<b>d'LIMONENE (5989-27-5)</b>	
IARC group	3 - Not classifiable
<b>Titanium Dioxide (13463-67-7)</b>	
IARC group	2B - Possibly carcinogenic to humans
<b>METHYL-ISOBUTYL KETONE (108-10-1)</b>	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

<b>METHYL-ISOBUTYL KETONE (108-10-1)</b>	
Specific target organ toxicity – single exposure	May cause respiratory irritation.

Specific target organ toxicity – repeated exposure : Not classified

<b>ethylbenzene (100-41-4)</b>	
Specific target organ toxicity – repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

Symptoms/effects after skin contact : May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

### SECTION 12: Ecological information

No ecotoxicological studies have been conducted on this product by Sumter Coatings.

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Flammable vapors may accumulate in the container.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint, 3, II

UN-No.(DOT) : UN1263

Proper Shipping Name (DOT) : Paint

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : II - Medium Danger



# 171T1000

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT)

: 3 - Flammable liquid



### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### 2-BUTANONE OXIME (96-29-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### XYLENE (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Subject to reporting requirements of United States SARA Section 313

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ

100 lb

##### ethylbenzene (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Subject to reporting requirements of United States SARA Section 313

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ

1000 lb

##### Naphtha (petroleum), hydrotreated heavy (64742-48-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### d'LIMONENE (5989-27-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### MINERAL SPIRITS R66/ D40 (64742-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Titanium Dioxide (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### METHYL N-PROPYL KETONE (107-87-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### AROMATIC 100 (64742-95-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### METHYL-ISOBUTYL KETONE (108-10-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Subject to reporting requirements of United States SARA Section 313

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ

5000 lb

##### AROMATIC 150 (64742-94-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### GLYCOL ETHER EP/PROPYL CELLOSOLVE SOLVENT (2807-30-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

##### CANADA

##### 2-BUTANONE OXIME (96-29-7)

Listed on the Canadian DSL (Domestic Substances List)

##### XYLENE (1330-20-7)

Listed on the Canadian DSL (Domestic Substances List)

##### ethylbenzene (100-41-4)

Listed on the Canadian DSL (Domestic Substances List)

# 171T1000

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **Naphtha (petroleum), hydrotreated heavy (64742-48-9)**

Listed on the Canadian DSL (Domestic Substances List)

### **d'LIMONENE (5989-27-5)**

Listed on the Canadian DSL (Domestic Substances List)

### **MINERAL SPIRITS R66/ D40 (64742-47-8)**

Listed on the Canadian DSL (Domestic Substances List)

### **Titanium Dioxide (13463-67-7)**

Listed on the Canadian DSL (Domestic Substances List)

### **METHYL N-PROPYL KETONE (107-87-9)**

Listed on the Canadian DSL (Domestic Substances List)

### **AROMATIC 100 (64742-95-6)**

Listed on the Canadian DSL (Domestic Substances List)

### **METHYL-ISOBUTYL KETONE (108-10-1)**

Listed on the Canadian DSL (Domestic Substances List)

### **AROMATIC 150 (64742-94-5)**

Listed on the Canadian DSL (Domestic Substances List)

### **GLYCOL ETHER EP/PROPYL CELLOSOLVE SOLVENT (2807-30-9)**

Listed on the Canadian DSL (Domestic Substances List)

### **EU-Regulations**

No additional information available

### **National regulations**

#### **ethylbenzene (100-41-4)**

Listed on IARC (International Agency for Research on Cancer)

#### **Titanium Dioxide (13463-67-7)**

Listed on IARC (International Agency for Research on Cancer)

#### **METHYL-ISOBUTYL KETONE (108-10-1)**

Listed on IARC (International Agency for Research on Cancer)

### **15.3. US State regulations**

**⚠ WARNING:** This product can expose you to METHYL-ISOBUTYL KETONE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# 171T1000

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Full text of H-phrases:

H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*