

SECTION 1: Identification
1.1. Identification

Product form : Mixture
 Product name : SC 90 HIGH GLOSS BLACK
 Product code : 882N0090

1.2. Recommended use and restrictions on use

Recommended use : Industrial use
 Restrictions on use : The product is intended for professional use

1.3. Supplier

Sumter Coatings, Inc.
 2410 Hwy 15 South
 Sumter, SC 29150 - United States
 T 803-481-3400 - F 803-481-3776
info@sumtercoatings.com - www.sumtercoatings.com

1.4. Emergency telephone number

Emergency number : 800-255-3924 Chemtel

SECTION 2: Hazard(s) identification
2.1. Classification of the substance or mixture
GHS US classification

Flammable liquids Category 1	H224	Extremely flammable liquid and vapor
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Germ cell mutagenicity Category 1B	H340	May cause genetic defects
Carcinogenicity Category 1A	H350	May cause cancer
Specific target organ toxicity (repeated exposure) Category 1	H372	Causes damage to organs through prolonged or repeated exposure

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements
GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H224 - Extremely flammable liquid and vapor
 H315 - Causes skin irritation
 H317 - May cause an allergic skin reaction
 H340 - May cause genetic defects
 H350 - May cause cancer
 H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground/Bond container and receiving equipment.
 P241 - Use explosion-proof electrical/ventilating/lighting equipment.
 P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.

882N0090

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
XYLENE	(CAS.No.) 1330-20-7	17.649 – 18.83	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
SOLVENT NAPHTHA MEDIUM ALIPHATIC	(CAS.No.) 64742-88-7	14.757 – 18.446	Flam. Liq. 3, H226 STOT RE 1, H372 Asp. Tox. 1, H304
VM&P NAPHTHA	(CAS.No.) 64742-89-8	5 – 10	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
ethylbenzene	(CAS.No.) 100-41-4	2.243 – 4.841	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304
METHYL N-PROPYL KETONE	(CAS.No.) 107-87-9	1 – 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319
Carbon Black, amorphous	(CAS.No.) 1333-86-4	1 – 5	Carc. 2, H351
Microcrystalline Silica in the form of Quartz	(CAS.No.) 14808-60-7	< 1.828	Carc. 1A, H350 STOT RE 2, H373
MINERAL SPIRITS R66/ D40	(CAS.No.) 64742-47-8	0.817 – 1.106	Flam. Liq. 3, H226 Asp. Tox. 1, H304
AROMATIC 100	(CAS.No.) 64742-95-6	0.1 – 1	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
Naphtha (petroleum), hydrotreated heavy	(CAS.No.) 64742-48-9	0.234 – 0.331	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
2-BUTANONE OXIME	(CAS.No.) 96-29-7	0.1 – 1	Flam. Liq. 4, H227 Acute Tox. 4 (Dermal), H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351

882N0090

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse eyes with water as a precaution.
- First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

- Fire hazard : Extremely flammable liquid and vapor.

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

882N0090

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

METHYL N-PROPYL KETONE (107-87-9)		
ACGIH	Local name	Methyl propyl ketone
ACGIH	ACGIH STEL (ppm)	150 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: Pulm func; eye irr
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m³)	700 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
AROMATIC 100 (64742-95-6)		
Not applicable		
MINERAL SPIRITS R66/ D40 (64742-47-8)		
Not applicable		
Naphtha (petroleum), hydrotreated heavy (64742-48-9)		
OSHA	OSHA PEL (TWA) (ppm)	400 ppm
Microcrystalline Silica in the form of Quartz (14808-60-7)		
ACGIH	Local name	Silica crystalline - quartz
ACGIH	ACGIH TWA (mg/m³)	0.025 mg/m³ (Respirable fraction)
ACGIH	Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2019
OSHA	Remark (OSHA)	Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1.
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
Carbon Black, amorphous (1333-86-4)		
ACGIH	Local name	Carbon black
ACGIH	ACGIH TWA (mg/m³)	3 mg/m³ (Inhalable fraction)
ACGIH	Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m³)	3.5 mg/m³
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
2-BUTANONE OXIME (96-29-7)		
Not applicable		
SOLVENT NAPHTHA MEDIUM ALIPHATIC (64742-88-7)		
Not applicable		
XYLENE (1330-20-7)		
ACGIH	Local name	Xylene, mixed isomers (Dimethylbenzene)
ACGIH	ACGIH TWA (ppm)	100 ppm

882N0090

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

XYLENE (1330-20-7)		
ACGIH	ACGIH STEL (ppm)	150 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
ethylbenzene (100-41-4)		
ACGIH	Local name	Ethylbenzene
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
VM&P NAPHTHA (64742-89-8)		
Not applicable		

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Color : Black
Odor : characteristic
Odor threshold : No data available
pH : No data available

882N0090

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 46 °F Based on data available for ingredients
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 7.88 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

VOC content : 4.22 lb/gal Based on data available for ingredients

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

METHYL N-PROPYL KETONE (107-87-9)	
LD50 oral rat	1600 – 3200 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral)
LD50 dermal rabbit	6500 mg/kg (Rabbit, Dermal)
LC50 inhalation rat (mg/l)	> 25.5 mg/l (OECD 436: Acute inhalation toxicity-acute toxic class method, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1600 mg/kg body weight
ATE US (dermal)	6500 mg/kg body weight

882N0090

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon Black, amorphous (1333-86-4)	
LD50 oral rat	> 8000 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	> 3000 mg/kg (Rabbit, Literature study, Dermal)
LC50 inhalation rat (mg/l)	> 4.6 mg/l air (4 h, Rat, Experimental value, Inhalation)

2-BUTANONE OXIME (96-29-7)	
LD50 oral rat	2326 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)
LD50 dermal rabbit	> 1000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	> 4.83 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours))
ATE US (oral)	2326 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight

SOLVENT NAPHTHA MEDIUM ALIPHATIC (64742-88-7)	
LD50 oral rat	> 5000 mg/kg body weight (Equivalent or similar to OECD 420, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	> 5.28 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours))

XYLENE (1330-20-7)	
LD50 oral rat	> 3608 mg/kg (Rat, Oral)
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	15432 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))
ATE US (oral)	3500 mg/kg body weight
ATE US (dermal)	15432 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	17.8 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.

Microcrystalline Silica in the form of Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans

Carbon Black, amorphous (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans

XYLENE (1330-20-7)	
IARC group	3 - Not classifiable

ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified

882N0090

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity – repeated exposure : Causes damage to organs through prolonged or repeated exposure.

Microcrystalline Silica in the form of Quartz (14808-60-7)

Specific target organ toxicity – repeated exposure : May cause damage to organs through prolonged or repeated exposure.

SOLVENT NAPHTHA MEDIUM ALIPHATIC (64742-88-7)

Specific target organ toxicity – repeated exposure : Causes damage to organs through prolonged or repeated exposure.

ethylbenzene (100-41-4)

Specific target organ toxicity – repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified
Viscosity, kinematic : No data available
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

SECTION 12: Ecological information

No ecotoxicological studies have been conducted on this product by Sumter Coatings.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint, 3, II
UN-No.(DOT) : UN1263
Proper Shipping Name (DOT) : Paint
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT) : II - Medium Danger
Hazard labels (DOT) : 3 - Flammable liquid



SECTION 15: Regulatory information

15.1. US Federal regulations

METHYL N-PROPYL KETONE (107-87-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

AROMATIC 100 (64742-95-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

MINERAL SPIRITS R66/ D40 (64742-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Naphtha (petroleum), hydrotreated heavy (64742-48-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Microcrystalline Silica in the form of Quartz (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

882N0090

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon Black, amorphous (1333-86-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
2-BUTANONE OXIME (96-29-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SOLVENT NAPHTHA MEDIUM ALIPHATIC (64742-88-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
XYLENE (1330-20-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	100 lb
ethylbenzene (100-41-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	1000 lb
VM&P NAPHTHA (64742-89-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. International regulations

CANADA

METHYL N-PROPYL KETONE (107-87-9)	
Listed on the Canadian DSL (Domestic Substances List)	
AROMATIC 100 (64742-95-6)	
Listed on the Canadian DSL (Domestic Substances List)	
MINERAL SPIRITS R66/ D40 (64742-47-8)	
Listed on the Canadian DSL (Domestic Substances List)	
Naphtha (petroleum), hydrotreated heavy (64742-48-9)	
Listed on the Canadian DSL (Domestic Substances List)	
Microcrystalline Silica in the form of Quartz (14808-60-7)	
Listed on the Canadian DSL (Domestic Substances List)	
Carbon Black, amorphous (1333-86-4)	
Listed on the Canadian DSL (Domestic Substances List)	
2-BUTANONE OXIME (96-29-7)	
Listed on the Canadian DSL (Domestic Substances List)	
SOLVENT NAPHTHA MEDIUM ALIPHATIC (64742-88-7)	
Listed on the Canadian DSL (Domestic Substances List)	
XYLENE (1330-20-7)	
Listed on the Canadian DSL (Domestic Substances List)	
ethylbenzene (100-41-4)	
Listed on the Canadian DSL (Domestic Substances List)	
VM&P NAPHTHA (64742-89-8)	
Listed on the Canadian DSL (Domestic Substances List)	

EU-Regulations

No additional information available

National regulations

Microcrystalline Silica in the form of Quartz (14808-60-7)	
Listed on IARC (International Agency for Research on Cancer)	

882N0090

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations


Carbon Black, amorphous (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)

ethylbenzene (100-41-4)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

 **WARNING:** This product can expose you to Carbon Black, amorphous, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.