



## SC 2000 Aluminum Tank Paint (888S2005)

### PRODUCT DESCRIPTION

**SC 2000 Aluminum Tank Paint** is a premium resin blend that was formulated with a maximum amount of aluminum to give years of service.

**SC 2000 Aluminum Tank Paint** provides an excellent finish for bulk storage tanks, customer tanks, pipes, as well as many other uses.

#### SC 2000 Aluminum Tank Paint Features

- Long Life
- Bright Finish
- Lead & Chrome Free
- Excellent Weather Durability
- Maximum Amount of Aluminum in Every Gallon

#### MIXING & APPLICATION

- Stir thoroughly prior to use.
- Brush, roll or spray.

**THINNING:** No thinning required.

**CLEAN UP:** XL Thinner (856X2210), Mineral Spirits (560X0194), or Xylene (560X3504).

**SPECIAL NOTE:** Product is water and moisture sensitive.

**ORDERING:** Available in single gallons and five gallon pails.

### TECHNICAL INFORMATION

**SURFACE PREPARATION:** Surface must be clean, dry, and free of dirt, grease, oil, loose rust, loose mill scale, and contaminants.

Recommend SSPC-SP-3 Power Tool Cleaning.

### PHYSICAL PROPERTIES

Type	Modified Oils
Components	One
Color	Aluminum
Volume Solids	46% ± 2%
Gloss	High
Coverage	735 sq ft/gal @ 1 mil 368 – 490 sq ft/gal @ recommended dft
Recommended DFT	1.5 – 2.0 mils dry film
VOC	Theoretical 3.60 lb/gal
Dry to Touch	1½ – 2 hours @ 77° F
Dry Tack Free	6 – 8 hours @ 77° F
Dry to Recoat	After 24 hours @ 77° F
Flash Point	In excess of 70° F
Temperature Resistance	Up to 400° F Continuously
Pot Life	N/A
Shelf Life	One year
Recommended Primer	Uni-Pox Primer or LV Uni-Pox Primer (Off White or Gray)

02/17

The technical data furnished are true and accurate to the best of our knowledge at the date of issuance. It is subject to change without prior notice. It is suggested the user verify with Sumter Coatings, Inc. prior to specifying or ordering. Test results are believed to be reliable; however, no guarantee of accuracy is given or implied. We guarantee all products to conform to Sumter Coatings, Inc.'s quality control standards. Liability, if any, is limited to replacement of product. No other warranty or guarantee of any kind, expressed or implied, is made by Sumter Coatings, Inc., including fitness for a particular purpose.