

SC 2110 STRONTIUM CHROMATE ALUMINUM (888S2006)

PRODUCT DESCRIPTION

SC 2110 Strontium Chromate Aluminum is a premium blend of resins containing a chromate paste that will provide a tough finish over marginally prepared surfaces. The chromate paste will act as an inhibitor to prevent corrosion.

SC 2110 Strontium Chromate Aluminum was developed primarily for tanks and cylinders, but may be used for many other applications.

ADVANTAGES OF SC 2110 STRONTIUM CHROMATE ALUMINUM

- Easy One Coat Coverage
- Can Be Used Without Primer
- Tarnish Resistant
- Holds Brightness
- Long Life

MIXING & APPLICATION

Stir thoroughly prior to and during use.

Brush, roll or spray.

THINNING: No thinning required.

CLEAN UP: XL Thinner (856X2210), Mineral Spirits (560X0194), or Xylene (560X3504).

SPECIAL NOTE: Product is water and moisture sensitive.

ORDERING: Available in single gallons and five gallon pails.

TECHNICAL INFORMATION

SURFACE PREPARATION: Surface must be clean, dry, and free of dirt, grease, oil, loose rust, loose mill scale, and contaminants.

Lightly sand surface or power tool clean.

PHYSICAL PROPERTIES

Type	Modified Oils
Components	One
Color	Aluminum
Volume Solids	45% ± 2%
Gloss	High
Coverage	730 sq ft/gal @ 1 mil 365 – 490 sq ft/gal @ recommended dft
Recommended DFT	1.5 – 2.0 mils dry minimum
VOC	Theoretical unreduced 3.75 lb/gal
Dry to Touch	1½ - 2 hours @ 77° F
Dry Tack Free	6 - 8 hours @ 77° F
Dry to Recoat	After 24 hours @ 77° F
Flash Point	In excess of 70° F
Temperature Resistance	Up to 400° F Continuous
Pot Life	N/A
Shelf Life	One year
Recommended Primer	Uni-Pox Primer or LV Uni-Pox Primer (Off White or Gray)

02/17

The technical data furnished are true and accurate to the best of our knowledge at the date of issuance. It is subject to change without prior notice. It is suggested the user verify with Sumter Coatings, Inc. prior to specifying or ordering. Test results are believed to be reliable; however, no guarantee of accuracy is given or implied. We guarantee all products to conform to Sumter Coatings, Inc.'s quality control standards. Liability, if any, is limited to replacement of product. No other warranty or guarantee of any kind, expressed or implied, is made by Sumter Coatings, Inc., including fitness for a particular purpose.